



A.R.K5FS DATA SHEET



SPECIFICATIONS & OPTIONS

Standards

- A.R.K series alternator conforms to the major international standards and specifications, including:
 - IEC60034, GB755, BS5000, VDE0530, NEMA, MG1-22, C22.2-100, CSA, AS1359 standard, etc.
- A.R.K series alternator is certified by ISO9001 quality system.
- A.R.K series alternator can be used for the generator set of CE mark.
- Other standards and certification can be based on customer requirements.

Electrical characteristics

- Insulation & Impregnating
Class H insulation.
All wound components are impregnated with material and processes designed specially to provide protection against harsh environments encountered in generator application. Resin based materials are selected and developed to provide the high build required for static windings and the high mechanical strength required for rotating components.
- 3-phase reconnectable with 12 ends brought out to the terminals.
- 2/3 pitch, can eliminate triple (3rd, 9th, 15th ...) harmonics on the voltage waveform and is found to be the optimum design for trouble-free supply of non-linear loads.
- Telephone interference
THF (as defined by IEC 60034-1) is less than 2%, TIF (as defined by NEMA MG1-32) is less than 50.
- Radio interference
Brushless device and the high quality AVR ensure low levels of interference with radio transmissions. RFI suppression module may be installed if required.
- High efficiency and motor startup capability.

Mechanical properties

- Steel structure.
 - Cast aluminum for front and rear cover.
 - Rigid assembly, effectively reduces the vibration during running.
 - All rotors are dynamically balanced to conform with BS6861.
 - Half key dynamic balance is applied in double bearing structure.
 - Non-maintenance sealed-for-life ball bearing.
 - 120% overspeed ability.
- Standard
Protection grade
- A.R.K series alternator protection level is IP23.
 - Suitable for environment with 95% relative humidity.
 - optional
 - Inlet and filter, power reduced by 5%.
 - Inlet and outlet filter, power reduced by 10% (IP44)
 - Anti-condensation heater.
 - Stator winding, bearing overheating protection.
 - Outlet line design of outlet box.
 - Center height can be customized according to requirements.

Excitation and voltage regulation system

MODEL	16 series	18 series	22 series	27 series	4 series	5 series	6 series	7 series
AVR								
SX460	Standard	Standard	Standard	Standard				
AS440(parallel optional)	Optional	Optional	Optional	Optional				
SX440(parallel optional)			Optional	Optional	Standard	Standard		
MX341(with PMG)			Optional	Optional	Optional	Optional		
MX321(with PMG)							Standard	Standard

With the self-excited system, the main stator provides power via the automatic voltage regulator (AVR) to the exciter stator. The high efficiency AVR ensures the voltage maintaining at the rated level. The exciter rotor output is fed to the main rotor through a three phase full wave bridge rectifier. The rectifier is protected by surge suppressor from voltage spikes of short circuit or phase mismatching.

Application

Prime power, rental, telecom, mobile power station, lighting tower, railway, refrigeration and standby power.

Quality assurance





A.R.K series alternators are manufactured using production procedures having a quality assurance level to ISO 9001.

Note: Continuous development of our products entitles us to change specification details without notice, therefore they must not be regarded as binding.





A.R.K5FS
Parameters (WINDING 311)

CONTROL SYSTEM				SELF EXCITED			
A.V.R.				MX341 WITH PMG			
VOLTAGE REGULATION				± 1.0 %			
SUSTAINED SHORT CIRCUIT				>300% OF RATED CURRENT			
INSULATION SYSTEM				H			
RATED POWER FACTOR				0.8			
PROTECTION				IP23			
STATOR WINDING				DOUBLE LAYER			
ROTOR WINDING				WITH DAMPING CAGE			
WINDING LEADS				12			
STATOR WDG. RESISTANCE				0.0043 Ohms PER PHASE AT 22°C SERIES STAR CONNECTED			
ROTOR WDG. RESISTANCE				1.96 Ohms at 22°C			
R.F.I. SUPPRESSION				BS EN 61000-6-2 & BS EN 61000-6-4, VDE 0875G, VDE 0875N. refer to factory for others			
WAVEFORM DISTORTION				NO LOAD < 1.5% NON-DISTORTING BALANCED LINEAR LOAD < 5.0%			
MAXIMUM OVERSPEED				2250 Rev/Min			
BEARING DRIVE END				BALL. 6220 - 2RS. (ISO)			
BEARING NON-DRIVE END				BALL. 6314 - 2RS. (ISO)			
1 BEARING				2 BEARING			
WEIGHT COMP. GENERATOR				1543 kg			
WEIGHT WOUND STATOR				722 kg			
WEIGHT WOUND ROTOR				617 kg			
WR* INERTIA				8.9828 kgm ²			
SHIPPING WEIGHTS in a crate				1635 kg			
PACKING CRATE SIZE				166 x 87 x 124(cm)			
50HZ				60HZ			
TELEPHONE INTERFERENCE				THF<2%			
COOLING AIR				1.035 m ³ /sec 2202 cfm			
VOLTAGE SERIES STAR				380/220			
VOLTAGE PARALLEL STAR				190/110			
VOLTAGE SERIES DELTA				220/110			
kVA BASE RATING FOR REACTANCE VALUES				625			
Xd DIR. AXIS SYNCHRONOUS				3.14			
X'd DIR. AXIS TRANSIENT				0.17			
X''d DIR. AXIS SUBTRANSIENT				0.12			
Xq QUAD. AXIS REACTANCE				2.45			
X''q QUAD. AXIS SUBTRANSIENT				0.26			
X L LEAKAGE REACTANCE				0.06			
X 2 NEGATIVE SEQUENCE				0.18			
X 0 ZERO SEQUENCE				0.08			
REACTANCES ARE SATURATED				VALUES ARE PER UNIT AT RATING AND VOLTAGE INDICATED			
T'd TRANSIENT TIME CONST.				0.08 s			
T''d SUB-TRANSTIME CONST.				0.012 s			
T'do O.C. FIELD TIME CONST.				2.5 s			
Ta ARMATURE TIME CONST.				0.019 s			
SHORT CIRCUIT RATIO				1/Xd			

A.R.K5FS
Three Phase Efficiency Curves (WINDING 311) 50HZ




A.R.K5FS
Three Phase Efficiency Curves (WINDING 311) 60HZ




A.R.K5FS
Locked Rotor Motor Starting Curve (Winding 311)

50_{Hz}




60_{Hz}



A.R.K5FS
Three-phase Short Circuit Decrement Curve. No-load Excitation at Rated Speed
Based on star (wye) connection.

50


Hz



Sustained Short Circuit = 2,900 Amps

60

Hz



Sustained Short Circuit = 3,300 Amps

1.The following multiplication factors should be used to adjust the values from curve between time 0.001 seconds and the minimum current point in respect of **nominal operating voltage**

50HZ		60HZ	
Voltage	Factor	Voltage	Factor
380V	X 1.00	416V	X 1.00
400V	X 1.06	440V	X 1.06
415V	X 1.09	460V	X 1.12
440V	X 1.12	480V	X 1.20

The sustained current value is constant irrespective of voltage level

2.The following multiplication factor should be used to convert the values calculated in accordance with NOTE 1 to those applicable to the various types of short circuit :

	3-phase	2-phase L-L	1-phase L-N
Instantaneous	x 1.00	x 0.87	x 1.30
Minimum	x 1.00	x 1.80	x 3.20
Sustained	x 1.00	x 1.50	x 2.50
Max. sustained duration	10 sec.	5 sec.	2 sec.

All other times are unchanged

3.Curves are drawn for Star (Wye) connected machines.

For other connection the following multipliers should be applied to current values as shown :

Parallel Star = Curve current value X 2

Series Delta = Curve current value X 1.732

A.R.K5FS
Winding 311 / 0.8 Power Factor
RATINGS

Class - Temp Rise		Cont. F - 105/40°C				Cont. H - 125/40°C				Standby - 150/40°C				Standby - 163/27°C			
50HZ	Series Star (V)	380	400	415	440	380	400	415	440	380	400	415	440	380	400	415	440
	Parallel S tar (V)	190	200	208	220	190	200	208	220	190	200	208	220	190	200	208	220
	Series Delta (V)□	220	230	240	254	220	230	240	254	220	230	240	254	220	230	240	254
	kVA	550	560	550	550	625	625	625	625	636	640	636	636	660	665	660	660
	Efficiency (%)	95	95.1	95.2	95.3	94.7	94.9	95	95.2	94.5	94.7	94.8	95	94.3	94.5	94.7	94.9
kW		440	448	440	440	500	500	500	500	509	512	509	509	528	532	528	528

Class - Temp Rise		Cont. F - 105/40°C				Cont. H - 125/40°C				Standby - 150/40°C				Standby - 163/27°C			
60HZ	Series Star (V)	416	440	460	480	416	440	460	480	416	440	460	480	416	440	460	480
	Parallel S tar (V)	208	220	230	240	208	220	230	240	208	220	230	240	208	220	230	240
	Series Delta (V)□	240	254	266	277	240	254	266	277	240	254	266	277	240	254	266	277
	kVA	625	650	663	675	681	713	731	775	719	750	780	800	738	769	798	819
	Efficiency (%)	95	95.1	95.3	95.3	94.8	94.9	95	95.1	94.6	94.7	94.8	94.8	94.5	94.6	94.7	94.8
	kW	500	520	530	540	545	570	585	620	575	600	624	640	590	615	638	655

DIMENSIONS

