



ARK6700Q 5kVA

Life Goes On...



DIESEL GENERATOR SETS

Type	Canopy
Phase	Single
Rated Frequency (Hz)	50
Rated Voltage (V)	230
Rated Power (kVA / kW)	4.5
Max Power (kVA / kW)	5,0
Power Factor	COS ϕ = 1
Rated Current (A)	19,6
Total Harmonic Content	$\leq 10\%$
Ambient Temperature	≤ -10 / $\leq 40^{\circ}\text{C}$
Insulation Class	F
DC Output (V)	12
DC Current (A)	8,3
Number of Poles	2
Excitation Type	AVR (Automatic Voltage Regulator), Brush
Dimensions L x W x H (mm)	910 x 530 x 840
Net Weight (kg)	149

ENGINE

Model	ARK186FA
Type	Air-Cooled, 4-Stroke, 1-Cylinder
Engine Power (hp)	7,9
Engine Speed (rpm)	3000
Bore x Stroke (mm)	86 x 72
Displacement (ml)	418
Compression Ratio	19,5:1
Fuel Type	Standard Diesel
Fuel Tank Capacity (L)	14,5
Fuel Consumption (l/h)	$\leq 1,75$
Continuous Running Time	7
Lubrication Quality	SAE10W30 (CD class and above)
Lubrication Type	Combined force - feed and splash lubrication
Starter	Electric Start
Noise level (dBA) at full load @ 1mt	78
Noise level (dBA) at full load @ 7mt	70

FEATURES / STANDART / OPTIONAL EQUIPMENTS

Fuel Level Gauge	√
Engine Start Key	√
Digital Multimeter	√
AC Circuit Breaker	√
Socket (2x16A)	√
Lamp	√
Wheels & Handler	√
Battery - 22Ah (For electrical start)	√
Counter	√
12V DC Outlet (100W)	√
DC Circuit Breaker	√
Remote Start	O
Automatic Transfer Switch	√
CE Certificate	√
20 Feet	72 Units
40 Feet HQ	144 Units