

## Output Ratings

Genset Model	Prime <sup>1</sup>	Standby <sup>2</sup>
415V, 60Hz	222kVA / 177,6kW	246,3kVA / 197,04kW

Ratings are given at 0,8 power factor

## Dimension & Weight

Length [mm]	Width [mm]	Height [mm]	Dry [kg]	Wet [kg]
2750/3640	1250/1250	1680/2100	1720/2370	-

Dry: With Lube Oil

Wet: With Lube Oil & Coolant

Without canopy/ with canopy

## Engine Technical Data

Engine Model :	Volvo TAD733GE
Number of Cylinders:	6 / Inline
Cycle :	4 Stroke
Bore / Stroke [mm] :	108 / 130
Induction :	Turbocharged CAC
Cooling Method :	Water
Governor Type :	Electronic
Compression Ratio :	18.1:1
Displacement [lt] :	7.15
Electrical Sys. Voltage	24V/Negative
Battery Charger Amps.	35A

## Lubrication System

Total Oil Capacity [lt] :	34
Oil Type :	API: CG-4, CH-4 15W-40
Oil Cooling Method :	Water

## Fuel System

Fuel Filter Type :	Replaceable Element
Recommended Fuel :	ASTM-D975-No1 and 2-D

## Fuel Consumption [lt] :

	110% Load	100% Load	75% Load	50% Load
60Hz	63,8	56,9	43,2	30,2

(Based on diesel fuel with a spec. gravity of 0,84 and complied with BS2869, Class A2)

## Alternator Data

Manufacturer :	Linz Electric
Model :	PRO28S B/4
No. of Bearings :	Single
Insulation Class:	H
Winding Pitch :	2/3
Number of Wire :	12
Protection Class :	IP23
Efficiency:	88,6%
Voltage Regulation (Steady State) :	1.0%
Total Harmonic Content:	4.0%
Apparent power [kVA]:	242

**1-Prime Rating:** These ratings are applicable for supplying continuous electrical power (at variable load) of commercially purchased power. There is no limitation to the annual hours of operation, this model can supply 10% overload power 1 hour in each 12 hours.

**2-Standby Rating:** These ratings are applicable for supplying continuous electrical power (at variable load) in the event of an utility power failure.No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528)

**Standard Reference Conditions:** Standart reference conditions 25°C Air Inlet Temp. 100m, 30% relative humidity.

## Cooling System

60Hz

Cooling System Capacity [lt] :	32
Heat rejected to Water & Lube Oil [kW]:	
Prime	99
Standby	110
Heat Radiation to Room [kW] :	
Prime	22
Standby	23
Radiator Fan Load [kW] :	13
Radiator Cooling Air Flow [m <sup>3</sup> /min] :	216
External Restrictions to :	
Cooling Airflow [Pa] :	300

## Exhaust System

60Hz

Max. Allowable Back Pressure [kPa] :	5
Exhaust Gas Flow [m <sup>3</sup> /min] :	
Prime	40.4
Standby	44.4
Exhaust Gas Temp. [ °C ] :	
Prime	509
Standby	530

## Performance

60Hz

Engine Speed [rpm] :	1800
Gross Engine Power [kW] :	
Prime	202
Standby	224.9

## Air Systems

50Hz

Air Filter Type :	Replaceable Element
Combustion Air Flow [m <sup>3</sup> /min] :	
Prime	14.2
Standby	15.7
Max. Combustion Air Intake	
Restriction [kPa] :	3.5

## Available Options

Arken offers a range of optional features to tailor our gensets to meet your power requirements.

Options:

- \* A wide range of Sound Attenuated Enclosures
- \* A variety of generating set control and synchronising panels
- \* Additional alarms and shutdowns
- \* A selection of exhaust silencer noise levels

For further information on all of the standard and optional features for this product, please contact ARKEN or visit [www.arkengenerator.com](http://www.arkengenerator.com)