

Output Ratings

Genset Model	Prime ¹	Standby ²
415V, 60Hz	258,4kVA / 206,72kW	286,2kVA / 228,96kW

Ratings are given at 0,8 power factor

Dimension & Weight

Length [mm]	Width [mm]	Height [mm]	Dry [kg]	Wet [kg]
2750/3640	1250/1250	1680/2100	1809/2460	-

Dry: With Lube Oil

Wet: With Lube Oil & Coolant

Without canopy/ with canopy

Engine Technical Data

Engine Model :	Volvo TAD734GE
Number of Cylinders:	6 / Inline
Cycle :	4 Stroke
Bore / Stroke [mm] :	108 / 130
Induction :	Turbocharged CAC
Cooling Method :	Water
Governor Type :	Electronic
Compression Ratio :	18:01
Displacement [lt] :	17:1
Electrical Sys. Voltage	24V/Negative
Battery Charger Amps.	100A

Lubrication System

Total Oil Capacity [lt] :	29
Oil Type :	API: CG-4, CH-4 15W-40
Oil Cooling Method :	Water

Fuel System

Fuel Filter Type :	Replaceable Element
Recommended Fuel :	ASTM-D975-No1 and 2-D

Fuel Consumption [lt] :

	110% Load	100% Load	75% Load	50% Load
60Hz	74,8	66,6	50,5	35,4

(Based on diesel fuel with a spec. gravity of 0,84 and complied with BS2869, Class A2)

Alternator Data

Manufacturer :	Linz Electric
Model :	PRO28S C/4
No. of Bearings :	Single
Insulation Class:	H
Winding Pitch :	2/3
Number of Wire :	12
Protection Class :	IP23
Efficiency:	93%
Voltage Regulation (Steady State) :	1.0%
Total Harmonic Content:	4.0%
Apparent power [kVA]:	270

1-Prime Rating: These ratings are applicable for supplying continuous electrical power (at variable load) of commercially purchased power. There is no limitation to the annual hours of operation, this model can supply 10% overload power 1 hour in each 12 hours.

2-Standby Rating: These ratings are applicable for supplying continuous electrical power (at variable load) in the event of an utility power failure.No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528)

Standard Reference Conditions: Standart reference conditions 25°C Air Inlet Temp. 100m, 30% relative humidity.

Cooling System

	60Hz
Cooling System Capacity [lt] :	32
Heat rejected to Water & Lube Oil [kW]:	
Prime	124
Standby	137
Heat Radiation to Room [kW] :	
Prime	25
Standby	28
Radiator Fan Load [kW] :	13
Radiator Cooling Air Flow [m ³ /min] :	336
External Restrictions to :	
Cooling Airflow [Pa] :	350

Exhaust System

	60Hz
Max. Allowable Back Pressure [kPa] :	10.0
Exhaust Gas Flow [m ³ /min] :	
Prime	36.7
Standby	37.9
Exhaust Gas Temp. [°C] :	
Prime	475
Standby	510

Performance

	60Hz
Engine Speed [rpm] :	1800
Gross Engine Power [kW] :	
Prime	243
Standby	263

Air Systems

	60Hz
Air Filter Type :	Replaceable Element
Combustion Air Flow [m ³ /min] :	
Prime	18.3
Standby	18.9

Max. Combustion Air Intake

Restriction [kPa] :	-
---------------------	---

Available Options

Arken offers a range of optional features to tailor our gensets to meet your power requirements.

Options:

- * A wide range of Sound Attenuated Enclosures
- * A variety of generating set control and synchronising panels
- * Additional alarms and shutdowns
- * A selection of exhaust silencer noise levels

For further information on all of the standard and optional

features for this product, please contact ARKEN or

visit www.arkengenerator.com