

Output Ratings

Genset Model	Prime ¹	Standby ²
415 V, 60 Hz	461,6 kVA / 369,28 kW	500 kVA / 400 kW

Ratings are given at 0,8 power factor

Dimension & Weight

Length [mm]	Width [mm]	Height [mm]	Dry [kg]	Wet [kg]
3350/4260	1300/1300	1730/1980	3175/3775	-

Dry: With Lube Oil

Wet: With Lube Oil & Coolant

Without canopy/ with canopy

Engine Technical Data

Engine Model :	Volvo TAD1344GE
Number of Cylinders:	6 / Inline
Cycle :	4 Stroke
Bore / Stroke [mm] :	131 / 158
Induction :	Turbocharged CAC
Cooling Method :	Water
Governor Type :	Electronic
Compression Ratio :	18.1:1
Displacement [lt] :	12.78
Electrical Sys. Voltage	24V/Negative
Battery Charger Amps.	80A

Lubrication System

Total Oil Capacity [lt] :	36
Oil Type :	API: CG-4, CH-4 15W-40
Oil Cooling Method :	Water

Fuel System

Fuel Filter Type :	Replaceable Element
Recommended Fuel :	ASTM-D975-No1 and 2-D

Fuel Consumption [lt] :

	110% Load	100% Load	75% Load	50% Load
60 Hz	111,0	101,2	76,6	53,8

(Based on diesel fuel with a spec. gravity of 0,84 and complied with BS2869, Class A2)

Alternator Data

Manufacturer :	Linz Electric
Model :	PRO28L G/4
No. of Bearings :	Single
Insulation Class:	H
Winding Pitch :	2/3
Number of Wire :	12
Protection Class :	IP23
Efficiency:	94.4%
Voltage Regulation (Steady State) :	1.0%
Total Harmonic Content:	4.0%
Apparent power [kVA]:	490

1-Prime Rating: These ratings are applicable for supplying continuous electrical power (at variable load) of commercially purchased power. There is no limitation to the annual hours of operation, this model can supply 10% overload power 1 hour in each 12 hours.

2-Standby Rating: These ratings are applicable for supplying continuous electrical power (at variable load) in the event of an utility power failure.No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528)

Standard Reference Conditions: Standart reference conditions 25°C Air Inlet Temp. 100m, 30% relative humidity.

Cooling System

60 Hz

Cooling System Capacity [lt] :	44
Heat rejected to Water [kW]:	
Prime	165
Standby	180
Heat Radiation to Room [kW] :	
Prime	22
Standby	23
Radiator Fan Load [kW] :	18
Radiator Cooling Air Flow [m ³ /min] :	360
External Restrictions to :	
Cooling Airflow [Pa] :	812

Exhaust System

60 Hz

Max. Allowable Back Pressure [kPa] :	9
Exhaust Gas Flow [m ³ /min] :	
Prime	77
Standby	82
Exhaust Gas Temp. [°C] :	
Prime	440
Standby	490

Performance

60 Hz

Engine Speed [rpm] :	1800
Gross Engine Power [kW] :	
Prime	410
Standby	449

Air Systems

60 Hz

Air Filter Type :	Replaceable Element
Combustion Air Flow [m ³ /min] :	
Prime	33
Standby	33

Max. Combustion Air Intake

Restriction [kPa] :	5.0
---------------------	-----

Available Options

Arken offers a range of optional features to tailor our gensets to meet your power requirements.

Options:

- * A wide range of Sound Attenuated Enclosures
- * A variety of generating set control and synchronising panels
- * Additional alarms and shutdowns
- * A selection of exhaust silencer noise levels

For further information on all of the standard and optional features for this product, please contact ARKEN or visit www.arkengenerator.com